


MODEL ZQ165 VENTILATION FAN



FEATURES -

BLOWER:

- Plug-in, permanently lubricated motor engineered for continuous operation
- Dynamically balanced centrifugal blower wheel for quiet, efficient performance
- Low RPM for quiet operation
- · Airflow-smoothing baffles reduce turbulence

HOUSING:

- Rugged, galvanized steel construction
- 6" round duct connector with tapered sleeve and no metallic clatter
- 7-5/8" height allows for 2" x 8" ceiling installations
- · Sturdy, easy, four-point mounting directly to joist
- Includes unique, patented spacer for mounting to engineered "!" joists
- Includes hanger bars to position housing anywhere between 16" to 24"-on-center joists
- Can be mounted in ceilings up to 12/12 pitch

GRILLE:


- Polymeric construction
- Innovative design the result of extensive research with designers and consumers


CONTROLS (Purchase separately):

 Refer to PennBarry's catalog for a complete line of accessories to effectively adapt these fans to your construction requirements.

U.L. Listed for use over bathtubs and showers when connected to a GFCI protected branch circuit (ceiling mount only).

DIMENSIONS











PennBarry | 605 Shiloh Rd. Plano, TX 75074 | 1 972-212-4700 | www.pennbarry.com

REFERENCE	QTY.	REMARKS	Project	
			Location	
			Architect	
			Engineer	
			Contractor	
			Submitted by	Date

PERFORMANCE RATINGS MODEL ZQ165 FAN

AMCA PERFORMANCE ————

Model	Static Pressure (Ps)	CFM	Sones	Fan Watts
70465	0.10	150	1.4	42.8
ZQ165	0.25	120		

AMPS —

Model	Amps
ZQ165	0.5

WEIGHT -

Model	Shipping Weight	
ZQ165	13.1 lbs	





AIR FLOW PERFORMANCE -

